

Description:

Cast-coated papers and boards for advertising, publishing and packaging.

End uses:

Folding materials, Industrial uses, RBP and film carriers, Retail labels, bags and packaging, Covers, Folders, Postcards, Brochures

Print methods:

Offset, Serigraphy, Rotogravure, Stamping, Flexo

Certificates:

- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Leitza mill](#)
- [ISO 14001 Environment](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety](#)

Technical specifications

Property	Test Method	Unit	Tolerance	180	200	250	300	350
Substance	ISO 536	g/m ² lbs	± 5%	180	200	250	300	350
				67	74	92	111	129
Thickness	ISO 534	µm points	± 5%	190	226	285	345	407
				7.5	8.9	11.2	13.6	16.0
Paper gloss 20	TAPPI T-653 pm-07	%	± 5	41	41	41	41	41
Brightness R457/D65	ISO 2470 / ISO 11475	%	± 2 / ± 5	89/108	89/108	89/108	89/108	89/108
Bekk smoothness (coated side)	ISO 5627	s	≥ 350	500	500	500	500	500
Cobb (uncoated side)	ISO 535	g/m ²	≤70	35	35	35	35	35
Relative humidity	TAPPI T502 om- 07	%	± 7	47	47	47	47	47

Values are subject to change without notice.

Last update: 06/28/2021