

Metalvac A HG

PRODUCT DATA SHEET

Description:

Metallized paper for self-adhesive labels with a high gloss finish.

End uses:

Label facestock, Wine and spirit labels

Print methods:

Offset, Rotogravure, Flexo

Certificates:

- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Leitza mill](#)
- [ISO 14001](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [OHSAS 18001 \(multisite\)](#)

Technical specifications

Property	Test Method	Unit	Tolerance	83
Substance	ISO 536	g/m ²	± 4 %	83
Thickness	ISO 534	µm	± 5	67
Gloss (silver, plain)	ISO 7668	%	± 25	620
Cobb (uncoated side)	ISO 535	g/m ²	± 5	23
Absolute humidity	ISO 287	%	± 1	4
Dry tensile strength MD	ISO 1924- 2	Kg/15mm	-1	7.5
Dry tensile strength CD	ISO 1924- 2	Kg/15mm	-0.5	4.4
Dry tear resistance MD/CD	ISO 1974	gf	-5.0	43/45

For other colors and finishes contact with specialty@lecta.com

Values are subject to change without notice.

Last update: 04/29/2019