

Creaset GP Light

TECHNICAL DATA SHEET

Description:

One-side coated grease proof gloss paper for standard and wraparound labeling.

End uses:

Retail labels, bags and packaging

Print methods:

Flexo, Offset

Certificates:

- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Motril mill](#)
- [ISO 14001 Environment](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety](#)
- [ISO 22000 Food Safety - Motril](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

Technical specifications

Property	Test Method	Unit	Tolerance	70	80	90
Substance	ISO 536 TAPPI T410	g/m ²	±4%	70	80	90
Thickness	ISO 534 TAPPI T411	µm	±4%	64	73	82
Parker roughness	ISO 8791-4 TAPPI T555	µm	<1.4	1.2	1.2	1.2
KIT (coated side)	TAPPI UM 559	index	-2	10	10	10
KIT (uncoated side)	TAPPI UM 559	index	-1	8	8	8
Paper gloss	ISO 8254-1 TAPPI T480	%	±5	68	68	68

**Service conditions must be consulted with the Commercial department for 100 gsm and 110 gsm.*

Values are subject to change without notice.

Last update: 11/17/2021