

Creaset HG HWS

TECHNICAL DATA SHEET

Description:

One-side coated high gloss paper for high wet-strength and alkali resistant labels.

End uses:

Labels for returnable bottles, Ice bucket resistant labels

Print methods:

Flexo, Offset, Rotogravure

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety](#)
- [ISO 22000 Food Safety - Motril](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Technical specifications

Property	Test Method	Unit	Tolerance	65	68	70	75	80
Substance	ISO 536	g/m ²	±4%	65	68	70	75	80
Thickness	ISO 534	µm	±4%	55	56,5	58	62,5	66
Paper gloss	ISO 8254-1	%	±5	76	76	76	76	76
Parker roughness	ISO 8791-4	µm	<1.1	0,8	0,8	0,9	0,9	0,9
Cobb (uncoated side)	ISO 535	g/m ²	±3	16	16	16	16	16
Alkaline wash off time	DIN 16524-6	sec.	max.	90	90	90	90	90
Alcali resistance	DIN 16524-7	min.	ref.	>60	>60	>60	>60	>60

Values are subject to change without notice.

Last update: 02/17/2023