

Creaset LWS

TECHNICAL DATA SHEET

Description:

One-side coated light wet strength gloss paper

End uses:

Labels for 1-way bottles

Print methods:

Flexo, Offset

Certificates:

- [Creaset Range List of certificates](#)
- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Motril mill](#)
- [ISO 14001 Environment](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety](#)
- [ISO 22000 Food Safety - Motril](#)

For applications that require specific certifications or approvals, please contact our sales teams.

Technical specifications

Property	Test Method	Unit	Tolerance	70	75	80
Substance	ISO 536	g/m ²	±4%	70	75	80
	TAPPI T410					
Thickness	ISO 534	µm	±4%	63.5	65	68
	TAPPI T411					
Parker roughness	ISO 8791-4	µm	<1.3	1.3	1.1	1.1
	TAPPI T555					
Cobb (uncoated side)	ISO 535	g/m ²	±3	20	20	20
	TAPPI T441					

Available in anti mould version on demand.

Values are subject to change without notice.
Last update: 04/04/2022