

Creaset Linen HWS

PRODUCT DATA SHEET

Description:

One-side coated embossed linen paper for high wet strength and alkali resistant labels

End uses:

Labels for returnable bottles, Ice bucket resistant labels

Print methods:

Flexo, Offset

Certificates:

- [CreaseLinenHWS CertificateConformity](#)
- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Motril mill](#)
- [ISO 14001](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [OHSAS 18001 \(multisite\)](#)
- [ISO 22000 Food Safety - Motril](#)

Technical specifications

Property	Test Method	Unit	Tolerance	65	70	75	80
Substance	ISO 536 TAPPI T410	g/m ²	±4%	65	70	75	80
Thickness	ISO 534 TAPPI T411	µm	±4%	55	59	63	67
Alcali resistance	DIN 16524-7	min.	ref.	>30	>30	>30	>30
Parker roughness	ISO 8791-4 TAPPI T555	µm	≥1.5	2.1	2.1	2.1	2.1
Cobb (uncoated side)	ISO 535 TAPPI T441	g/m ²	±3	14	14	14	14
Alkaline wash off time	DIN 16524-6	sec.	max.	90	90	90	90

Values are subject to change without notice.
Last update: 04/29/2019