

Creaset Litho (North America)

TECHNICAL DATA SHEET

Description:

One-side coated high gloss paper, with post-consumer pulp content for standard and wraparound labelling.

End uses:

Wraparound labels, Folding materials, Labels for 1-way bottles, Flexible packaging

Print methods:

Flexo, Offset

Certificates:

- [Creaset Range List of certificates](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [EMAS Motril mill](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety](#)
- [ISO 22000 Food Safety - Motril](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.



Creaset Litho (North America)

TECHNICAL DATA SHEET

Technical specifications

| Property | Test Method | Unit | Tolerance | 60# | 70# | 80# | 95# |
|----------------------------------|---|------------------|---------------------------|---------|---------|---------|---------|
| Substance | ISO 536 TAPPI T410 | g/m ² | ±4% | 89 | 104 | 118 | 140 |
| Thickness (µm) | ISO 534 TAPPI T411 | µm | ±4% | 80 | 93 | 107 | 127 |
| Thickness (pt.) | ISO 534 TAPPI T411 | pt. | ±4% | 3.2 | 3.7 | 3.9 | 5 |
| Bekk smoothness (coated side) | ISO 5627 TAPPI T475 (#) TAPPI T479(*) | sec. | -150 (#) >0,70*STD (*) | 750 (D) | 600 (D) | 420 (*) | 600 (*) |
| Brightness R457/D65 | ISO 2470-2 | % | ± 2 | 92 | 92 | 93 | 94 |
| Cobb (uncoated side) | ISO 535 TAPPI T441 | g/m ² | ±4 | 25 | 26 | 24 | 25 |

Only for North America market

Values are subject to change without notice.
Last update: 02/17/2023